



# WAERDSE TEMPEL

## TECHNICAL RIDER

STRAND VAN LUNA 1  
1704 ZZ HEERHUGOWAARD  
TEL: +31 (0)72 5721363 / FAX: +31 (0)72 57213878

### Main hall

Capacity	: 2500		
Max sound level	: 105 DbA	Please note: limiters will be inserted on outputs if this level is exceeded.	
Stage	: Permanent stage 8 m x 24 m Height 1.45m Clearance 7.00m		
Power supply	: Light	Sound	Various
All CEEform 5p and 3p	1 * 125A/400V 2 * 63A/400V 2 * 32A/400V 3 * 16A/230V	1 * 63A/400V 2 * 32A/400V 3 * 16A/230V	2 * 32A/400V stage right 2 * 32A/400V stage left

### Standard PA specs

per side	: 8x Electro Voice Xlc 127dvx compact line array 5x Electro Voice X-sub placed under stage	
Processing	: Klark Teknik DN-9848	
Amps	: Electro Voice CP-3000s for XLC Electro Voice P-3000 for X-subs	
Foh Desk	: Midas Heritage 2000 44 + 4 stereo (48 ch. multi + 12 ch. return multi)	
Equalisers	: Klark Teknik Square One Graphic EQ 2x30 bands on main system	
Dynamics/inserts	: 2x Klark Teknik DN-504 + quad compressor 2x Klark Teknik DN 514 + 4-channel auto gate	
Players/Recorders	: Tascam CD-RW 750 / Tascam MD-350 19"	
Effects	: 1x Lexicon PCM-91 1x TC Electronics M2000 1x TC Electronics D-two 1x Yamaha SPX-2000	
Monitor Desk	: Midas Siena 480 48 mono channels, 16 output groups 2x Klark Teknik DN9244E 4 channel Digital Limiting and	

## Standard light: Main hall

Controller : Avolites Pearl 2004 (position can be DJ Booth or FOH or backstage)  
Dimmers : 72x 2,5Kw LSC Epro including patchpanel  
Lamps : 108x ETC SourceFour Par 750 Watt Long life (18x6-bar Connex)  
: 4x ADB CH20 45° -90° 2Kw Fresnel including Barndoors  
: 4x ADB DS204 13° -36° 2Kw Profile  
: 16x Par64 c/w colorframe (4x 4-bar Connex)  
: 2 x Audience 4-light Blinder 2,5Kw  
: 2x PAR 64 ACL-set Short-nose  
: 2x 4-lite-blinder  
Intelligent : 6x Martin MAC700 Profile  
: 6x Martin MAC600 Washlight  
: 2x Martin Atomic 3Kw Strobelight  
: 1x JEM ZR33 Fogmachine  
: 1x Swefog Ultimate 200 Oilcracker  
Projector : 1x 3000 Ansi.  
Rigging : 4x 16 mtr. Prolyte H30V Truss (above stage and front stage)  
: 3x Loadstar 1T Electromotor including controller/truss  
: 10x 10 mtr square grid, above audience/4x lodestar 1T  
Backdrop : 24 mtr. X 8,50 mtr. , On each side: 2x 4mtr x 8,50 mtr.

## Small venue

Capacity : 350

Max sound level : 105 DbA  
Please note: limiters will be inserted on outputs if this level is exceeded.

Stage : Permanent stage 4 m x 6 m Height 40 cm

Clearance : 2.50 m (height)

Power supply	Light	Sound	Various
All CEEform 5p and 3p	1 * 125A/400V	1 * 63A/400V	2 * 32A/400V stage right
	2 * 63A/400V	2 * 32A/400V	2 * 32A/400V stage left
	2 * 32A/400V	3 * 16A/230V	
	3 * 16A/230V		

## Standard PA specs:

per side : 2x Electro Voice RX-212 top (2x" + 3" HF total 650 W aan 108 dB) 2x Electro Voice RX-sub (1x 18" 600 W / 8 Ohm)

Processing : Electro Voice DX38 systeem processor

Amps : 2x Electro Voice CP-3000s 2x Electro Voice CP-2200